

Pressure Gauge DN40 SS

Type P1109 – Plus Line

Date: November 2005

Sheet No.: 1-329GB



Pressure gauge all stainless steel

- All kind of industrial services
- Liquid-filled to damp vibrations
- Rear or bottom connection
- Direct mounting
- 1/8" or 1/4" NPT thread connection
- Scale in accordance with international standard
- All Stainless steel design

Application

The TEMPRESS DN40 SS Plus Line pressure gauges is made to be used in all kind of industrial applications such as chemical, petrochemical, pulp and paper mills, power generating, hydraulic and pneumatic machinery, offshore platforms and OEM equipment.

Availability

The Tempress DN40 SS pressure gauge is available from stock in 12 specifications.

Specifications	
Pressure Gauges:	DN 40 type P1109
Case material:	Stainless steel, AISI 304
Front glass:	Polycarbonate
Front ring:	Stainless steel, AISI 304
Liquid filling:	Glycerine
Connection:	1/4" or 1/8" NPT
Measuring system:	AISI 316
Measuring range:	0-2,5 / 0-4 / 0-7 / 0-11 Bar
Other ranges:	on request
Accuracy:	± 2.5% FS
Scale:	Bar/Psi

TEMPRESS reserves the right to changes without notice

Agent/Dealer:



001

TEMPRESS A/S

Nordlandsvej 64-66
 DK-8240 Risskov, Denmark
 Tel.: +45 8932 5210
 Fax.: +45 8932 5213
 sales@tempress.dk
 www.tempress.dk