



Data sheet	Instrument	Type	DN	A	B	C	LI	Min. span	Max. pressure
1-600	Pressure Gauge	A32, A33, A37	65	Ø77,5	10	Ø60,3	156	1 bar (15 psi)	40 bar (580 psi)
			50	Ø64	10	Ø48,6	156	1 bar (15 psi)	40 bar (580 psi)
			40	Ø50,5	10	Ø35,6	120	1 bar (15 psi)	40 bar (580 psi)
2-600	Pressure Transmitter	P1232, P1235	25	Ø50,5	10	Ø22,6	120	1 bar (15 psi)	40 bar (580 psi)

Transmission liquid			
Application	Liquid type	Temp range	Span
Standard	Glycerine 90/10	-5/+130 °C (+23/+266 °F)	All
Low temperature	Glycerine 75/25	-40/+100 °C (-40/+212 °F)	All
High temperature	Glycerine	+5/+200 °C <sup>a</sup> (+41/+392 °F)	≥4 bar (60 psi)

Diaphragm seal			
Diaphragm seal	TR	...	...
<b>Wetted parts in AISI 316L</b>			
DN 25		<b>36</b>	
DN 40		<b>37</b>	
DN 51		<b>38</b>	
DN 65		<b>39</b>	
<b>Diaphragm</b>			
AISI 316L			<b>04</b>
AISI 316L electropolished			<b>08</b>
<b>Example</b>			
Diaphragm seal with wetted parts and diaphragm in AISI 316			<b>TR3704</b>



74-02

3-A approval is available for P1232 and most pressure gauges in DN 100, see 1-601GB

TEMPRESS reserves the right to changes without notice

Agent/Dealer:



## TEMPRESS A/S

Nordlandsvej 64-66  
 DK-8240 Risskov, Denmark  
 Tel.: +45 8932 5210  
 Fax.: +45 8932 5213  
 sales@tempress.dk  
 www.tempress.dk